

# **ODA-144MH**

**POWER RANGE** 

430W~460W

**CELL SIZE** 

166\*83mm



### **JUNCTION BOX**

Waterproof protection grade: IP67/IP68 Safety Level: Class II Maximum System Voltage: 1500V outstanding waterproof level Effectively resist harsh environments



#### Frame

Strong machinical load resistance up to 5400Pa Anodic oxidation layer resistant to chemical corrosion available in silver and black
























·IEC61215 / · IEC61730

### WARRANTY





Guarantee on product materail and workmanship



Linear Power output warranty



9BB





## Half-cut Technology

New circuit design, lower internal current and lower internal resistance loss



### Significantly avoiding heat spot

The unique circuit design to reduce the temperature of heat spot significantly, so that to reduce the power loss and then increase the output of modules.



#### **Lower cost**

Increasing power generation can reduce the cost per kilowatt-hour



### **Excellent performance of PID resistance**

The performance of PID resistance(Potential Induced Degradation) passed the standard of TUV Nord.

# NINGBO OSDA SOLAR CO.,LTD www.osdasol.com

OSDA Solar established in 2008, is a high-tech enterprise integrating R&D, production and sales of solar energy products. It is committed to the overall solution of distributed photovoltaic system and provides services from consulting, design, construction, financing to intelligent operation and maintenance.


OSDA has 3 production sites in China and branches and representative offices in more than 10 countries overseas. Products include solar cells, modules, On/Off grid solar system, solar pump and other solar related applications. Our products have passed many international certifications such as TVM, MCS, CEC, IEC, ISO, CE, CQC and so on. With excellent quality, our products are exported to more than 100 countries of the world.


Since its establishment, OSDA has always followed the idea of "Smart energy · Lightening future". It has followed the steps of "the Belt and Road Initiative", we bring bright light to the countries and people who are short of electricity. Sharing the concept of modern civilization, and building a green home together.

# **ODA-144MH**


### **PV DRAWINGS**

Unit:mm





### IV CURVE (440W)



# **ELECTRICAL DATA (STC)**

Model Type	ODA430-36V-MH	ODA440-36V-MH	ODA450-36V-MH	ODA460-36V-MH
Peak Power(Pmax)	430.00	440.00	450.00	460.00
Maximum Power Voltage(Vmp)	40.70	41.10	41.50	41.90
Maximum Power Current(Imp)	10.57	10.71	10.85	10.99
Open Circuit Voltage(Voc)	48.50±3%	48.90±3%	49.30±3%	49.70±3%
Short Circuit Current(Isc)	11.31±3%	11.46±3%	11.60±3%	11.72±3%
Module Efficiency( % )	19.78	20.24	20.70	21.16

 $<sup>^{\</sup>star}$  STC: irradiance 1000 W/m², AM 1.5, and cell temperature of 25°C

# ELECTRICAL DATA (NOCT)

Model Type	ODA430-36V-MH	ODA440-36V-MH	ODA450-36V-MH	ODA460-36V-MH
Peak Power(Pmax)	321.10	328.60	336.10	343.50
Maximum Power Voltage(Vmp)	37.90	38.30	38.60	39.00
Maximum Power Current(Imp)	8.47	8.59	8.70	8.80
Open Circuit Voltage(Voc)	45.50±3%	45.80±3%	46.20±3%	46.60±3%
Short Circuit Current(Isc)	9.15±3%	9.27±3%	9.38±3%	9.48±3%

<sup>\*</sup> NOCT: irradiance 800 W/m², AM 1.5, ambient temperature 20°C, wind speed 1 m/s

### **TEMPERATURE & MAXIMUM RATING**

Maximum System Voltage (V)	1500 V
Maximum Series Fuse Rating (A)	20 A
Power Tolerance	0~+3 W
Pmax Temperature Coefficients (W/°C)	-0.350 %/°C
Voc Temperature Coefficients (V/°C)	-0.270 %/°C
Isc Temperature Coefficients (A/°C)	+0.048 %/°C
NOCT Nominal Operating Cell Remperature (°C)	45±2 ℃
Operating and Storage Temperature (°C)	-40~+85 °C

### **MECHANICAL CHARACTERISRTICS**

Cell Type	166*83 Mono
No. of Cells	144 (12*12)
Dimensions	2094*1038*35mm
Weight	23.50kg
Front Glass	3.2mm high transmission, low iron, tempered glass
Frame	Anodized Aluminium Alloy
Junction box	IP67/IP68 3diodes
Output cables	4mm <sup>2</sup> cable 35cm (Inlcuding MC4 connector)
MaxWind Load/Snow Load	2400Pa/5400Pa

### **PACKING WAY**

20FT container	5 Packages/155pcs
40HQ container	22 Packages/726pcs





We Are Seeking Agents And Partners!

ADD: NO.128 Haichuan Rd, Jiangbei Dist., Ningbo, China

Tel: 86-574-87915068
Call: 86-13566302808
E-mail: sales@osdasol.com
The company reserves the right of final interpretation, November 2020 edition